


SMP 25 mm DEFLECTION ISOLATOR

S-I UNITS (mm AND kg)

TYPE	A	B	C	D	E	F	G	H	L	W
50C/3500C	203	44	11	16	51	191	11	127	229	89

NOTE: ALL MOUNTING DIMENSIONS SYMMETRIC ABOUT ISOLATOR CENTER

STANDARD RATINGS		SPRING COIL					
		COLOR		FREE		RATED	
TYPE	SIZE	OUTER	INNER	HT.	O.D.	LOAD	DEFL.
SMP	50C	BEIGE		107	76	23	25
SMP	100C	CHROME		107	76	45	25
SMP	250C	BLUE		107	76	113	45
SMP	450C	GREEN		107	76	204	39
SMP	625C	BLACK		107	76	283	37
SMP	800C	GRAY		107	76	363	33
SMP	1000C	RED		107	76	454	29
SMP	1250C	BROWN		107	76	567	28
SMP	1700C	ORANGE		107	76	771	24
SMP	2200C	ORANGE	GRAY	107	76	998	26
SMP	2465C	BLUE		107	76	1118	25
SMP	2865C	BLUE	GRAY	107	76	1300	25
SMP	3500C	BLUE	BROWN	107	76	1588	25



SPECIFICATIONS:

- HOUSED COIL SPRING ISOLATOR WITH ADJUSTABLE SNUBBERS.
- POWDER COATED STEEL SPRING ELEMENTS.
OTHER METALLIC HARDWARE IS BRIGHT ZINC PLATED.
- HOUSINGS ARE POWDER COATED CAST IRON.
- MINIMUM OVERLOAD OF 50%.
- MINIMUM K_x/K_y RATIO OF 1.0.
- ALL ELEMENTS SAFE AT SOLID LOADING.
- ALL THREADED MEMBERS ARE AMERICAN STANDARD.



KINETICS NOISE CONTROL, INC
6300 IRELAN PL,
DUBLIN, OH 43017 USA
Ph: 614 889-0480, Fax: 614 889-0540
www.kineticsnoise.com

Model:
**SMP-
50C/3500C**

By: BB
Date: 02/11/08
Revised: /

Drawing No:
**S-01.25-12
METRIC**