



- HS-1 SNUBBER IS PAINTED GRAY CARBON STEEL.
- HS-1 SNUBBER INCORPORATES A NEOPRENE SNUBBING PAD.

HS-1 DIMENSIONAL DATA

| MODEL | DIMENSION | | | | | | | | | | | | | | ANCHOR BOLT DIA. (2 REQ'D) | | | |
|-----------|-----------|-----|------|-----|------|----|-------|-----|------|-----|------|----|------|----|----------------------------|----|------|----|
| | A | | B | | C | | D | | E | | F | | G | | H | | in | mm |
| | in | mm | in | mm | in | mm | in | mm | in | mm | in | mm | in | mm | in | mm | | |
| HS-1-2000 | 4.22 | 107 | 3.00 | 76 | 0.50 | 13 | 8.00 | 203 | 6.00 | 152 | 1.00 | 25 | 1.72 | 44 | 0.56 | 14 | 0.50 | 13 |
| HS-1-4000 | 6.22 | 158 | 4.00 | 102 | 0.75 | 19 | 9.50 | 241 | 7.50 | 191 | 1.00 | 25 | 2.22 | 56 | 0.69 | 17 | 0.63 | 16 |
| HS-1-6000 | 6.22 | 158 | 4.00 | 102 | 0.75 | 19 | 12.00 | 305 | 9.00 | 229 | 1.50 | 38 | 2.22 | 56 | 0.81 | 21 | 0.75 | 19 |

HS-1 CAPACITY DATA

| MODEL | CONCRETE ATTACHMENT* | | | | | | STEEL ATTACHMENT | | | |
|-----------|----------------------|------|-------|------|------|------|------------------|------|-----------|------|
| | KAAB | | KCCAB | | KCAB | | WELDED** | | BOLTED*** | |
| | lb | kg | lb | kg | lb | kg | lb | kg | lb | kg |
| HS-1-2000 | 1598 | 725 | 1956 | 887 | 1031 | 468 | 3094 | 1403 | 3094 | 1403 |
| HS-1-4000 | 2792 | 1266 | 2893 | 1312 | 1858 | 843 | 6581 | 2985 | 6581 | 2985 |
| HS-1-6000 | 3989 | 1809 | 4367 | 1981 | 2457 | 1114 | 8404 | 3812 | 8404 | 3812 |

* 3000 PSI (211 kg/cm²) NORMAL WEIGHT CONCRETE.

** USE MINIMUM E60XX WELD ELECTRODES.

*** USE ASTM A307 OR A325 BOLTS.

